AUTOMOTIVE
LOW VOC SPECIALTY REDUCER

DESCRIPTION AND USES

Rust-Oleum® Low VOC Specialty Reducer is a high-solvency thinner designed to thin Rust-Oleum Primer Surfacer for easy spray application. Carefully read all directions, notes and cautions prior to use.

PRODUCTS

SKU	Description
261192	1-Quart

PRODUCT APPLICATION

INSTRUCTIONS

Use as a reducer when recommended by the product manufacturer. Stir Primer Surfacer before adding Specialty Reducer. Mix one part of Primer Surfacer with one part of Specialty Reducer. Do not use more than recommended. Protect hands with solvent-resistant gloves and eyes with safety glasses. Stir the mixture thoroughly. The product is now ready to be used in a spray gun.

Note: Most automotive finishes require a specific thinner for use within certain temperature ranges. Specialty Reducer has a medium rate of drying when used within mid-range temperature conditions.

Form: GDH-34
Rev.: 041213

TECHNICAL DATA

AUTOMOTIVE LOW VOC SPECIALTY REDUCER

PHYSICAL PROPERTIES

		LOW VOC SPECIALTY REDUCER
Solvent Type		Blend of Acetone, Siloxane and Oxsol
Weight	Per Gallon	6.75 lbs.
	Per Liter	0.81 kg
VOC		0 g/l
Shelf Life		5 years
Flash Point		-4°F (-20°C)
Safety Information		**FOR ADDITIONAL INFORMATION, SEE MSDS**

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-34
Rev.: 041213